

***In the Drawings:***

It is requested that the examiner approve the proposed amendment to Figures 4 and 7 indicated in red on the attached copy of those figures.

***In the Specification:***

On page 8 line 7, please delete "L" and insert "LL". (Done by informal ex. amt.)

***In the Claims:***

Please amend claims 1-6, 8-11, 13, 15-16 and 18-20, add claim 21, and cancel claim 14, leaving claims 1-13 and 15-21 in the case. The amended claims are shown in marked up form in Exhibit A.

1. (Amended.) An electrical terminal, comprising:
- (a) a crimp flange having a pair of upwardly directed opposite side portions and a bottom portion extending between and interconnecting said side portions;
  - (b) at least one insulation piercing knife integral with said crimp flange projecting from said bottom portion into the space between said side portions; and
  - (c) a blade extending from said crimp flange for insertion into an electrical socket.
2. (Amended.) The terminal of Claim 1 wherein said at least one insulation piercing knife is a pair of insulation piercing knives cut out and bent upwardly from said bottom portion of said crimp flange.
3. (Amended.) The terminal of Claim 2 wherein said insulation piercing knives are disposed substantially in a tandem alignment with one another.

4. (Amended.) The terminal of Claim 1 wherein said blade includes a web portion connected to said crimp flange and a plurality of abutting undulations formed along opposite sides of said web portion defining barbs for abutting against a plug housing to resist removal of said electrical terminal therefrom.

5. (Amended.) An electrical plug assembly, comprising:

(a) a plug housing having opposite ends and defining a pair of spaced apart channels therethrough open at each of said opposite ends thereof;

(b) a pair of insulated conductors each having an end and an electrical wire and a layer of insulation covering said wire and being disposed at least partially within one of said channels of said plug housing; and

(c) a pair of electrical terminals each being insertable into one of said channels of said plug housing at one of said opposite ends of said plug housing, each said terminal including:

(i) a crimp flange having a pair of upwardly directed opposite side portions and a concave arcuate-shaped bottom portion extending between and interconnecting said side portions;

(ii) at least one insulation piercing knife integral with said crimp flange projecting upwardly from said bottom portion into the space between said side portions; and

(iii) a blade extending from said crimp flange for insertion into an external electrical socket for making an electrical connection.

6. (Amended.) The assembly of Claim 5 wherein said housing is of a one-piece construction.

8. (Amended.) The assembly of Claim 5 wherein:  
each of said electrical terminals has opposite ends; and  
said crimp flange of each said electrical terminal is disposed at a rearward position on said electrical terminal adjacent to one of said opposite ends thereof.

9. (Amended.) The assembly of Claim 8 wherein said blade of each of said electrical terminals is disposed at a forward position on said electrical terminal opposite from said crimp flange and adjacent to the other of said opposite ends of said electrical terminal and extending therefrom toward but spaced from said one opposite end of said electrical terminal.

10. (Amended.) The assembly of Claim 5 wherein said at least one insulation piercing knife of said electrical terminal is a pair of insulation piercing knives cut out and bent upwardly from said bottom portion of said crimp flange of said electrical terminal and disposed said side portions of said crimp flange of said electrical terminal.

11. (Amended.) The terminal of Claim 10 wherein said insulation piercing knives are disposed substantially in a tandem alignment with one another.

13. (Amended.) A method of making a plug assembly, said method comprising the steps of:

(a) providing a plug housing and a plurality of electrical terminals, each of the electrical terminals having a crimp flange, at least one insulation piercing knife connected to the crimp flange and a blade connected to the crimp flange for insertion into an external electrical socket, the crimp flange having a pair of upwardly directed

43  
BA

opposite side portions and a bottom portion extending between and interconnecting the side portions, the knife extending upwardly from the bottom portion of the crimp flange and disposed of the side portions of the crimp flange such that the end of the insulated conductor can be placed between the side portions of the crimp flange and over the piercing knife whereupon prior to insertion of the electrical terminal into the respective one of the channels of the plug housing the crimp flange is crimped onto the insulated conductor end by bending the side portions of the crimp flange toward one another over and downwardly toward the insulated conductor end such that the side portions of the crimp flange press the insulated conductor end downwardly upon the piercing knife which pierces and displaces insulation of the insulated conductor end and makes an electrical connection with an electrical wire of the insulated conductor and such that after crimping the crimp flange the electrical terminal may be inserted into the channel of the plug housing at the one of opposite ends of the plug housing to a point spaced interiorly from the other of the opposite ends of the plug housing;

(b) passing a pair of insulated conductors through channels of the plug housing such that separate portions of each of the insulated conductors extend from opposite ends of the plug housing;

(c) aligning ends of the electrical terminals with the portions of the insulated conductors which extend from one of the opposite ends of the plug housing;

(d) crimping the electrical terminals on the ends of the insulated conductors such that insulation on the insulated conductors is penetrated and electrical connections

are made between the electrical terminals and electrical wires within the ends of the insulated conductors; and

securing the crimped electrical terminals on the insulated conductor ends within the channels of the plug housing.

15. (Amended.) The method of Claim 14 wherein said electrical terminal is provided with a pair of insulation piercing knives cutout and bent upwardly from the bottom portion of the crimp flange.

16. (Amended.) The method of Claim 15 wherein said insulation piercing knives are provided substantially in a tandem alignment with one another.

18. (Amended.) The method of Claim 13 wherein the terminals are provided with an interconnecting strip and the strip is removed concurrently with said crimping of the electrical terminals.

19. (Amended.) The method of Claim 13 wherein the terminals are provided with an interconnecting strip and the strip is removed after the crimping of the electrical terminals.

20. (Amended.) The method of Claim 13 wherein the terminals are provided with an interconnecting strip and the strip is removed before the crimping of the electrical terminals.

21. (New.) The terminal of claim 1 in which the bottom portion is concave shaped.